

SAFETY DATA SHEET



1. Identification

Product number K33
Product identifier **RAZOR**
Distributed By: Kayline Company
PO Box 603207
Cleveland, Ohio 44103
Company phone General Assistance 216-566-9858
Emergency telephone US 1-800-535-5053

Version # 01
Recommended use Not available.
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 2
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Call a poison center/doctor. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methylene Chloride		75-09-2	60 - 80
Butane		106-97-8	2.5 - 10
Methanol		67-56-1	2.5 - 10
Propane		74-98-6	2.5 - 10
Toluene		108-88-3	2.5 - 10
Propylene Oxide		75-56-9	0.1 - 1
Other components below reportable levels			1 - 2.5

#: This substance has workplace exposure limit(s).

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Remove and isolate contaminated clothing and shoes. Immediately flush skin with plenty of water. Call a physician or Poison Control Center immediately. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Call a physician or Poison Control Center immediately.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth thoroughly. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Dizziness. Nausea. Irritation of eyes and mucous membranes. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

In case of shortness of breath, give oxygen. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep victim under observation. Keep victim warm.

5. Fire-fighting measures

Suitable extinguishing media

Not available.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not direct water at source of leak or safety devices as icing may occur. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Consider initial downwind evacuation for at least 500 meters (1/3 mile). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. May be ignited by open flame. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid exposure - obtain special instructions before use. Do not breathe mist or vapor. Do not breathe gas. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid contact with eyes, skin, and clothing. Avoid prolonged and repeated contact. Avoid prolonged exposure. Do not get this material on clothing. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Keep locked up. Avoid exposure - obtain special instructions before use. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Methylene Chloride (CAS 75-09-2)	STEL	125 ppm
	TWA	25 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Methanol (CAS 67-56-1)	PEL	260 mg/m3
		200 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
Propylene Oxide (CAS 75-56-9)	PEL	240 mg/m3
		100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Methylene Chloride (CAS 75-09-2)	TWA	50 ppm
Propylene Oxide (CAS 75-56-9)	TWA	2 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Methanol (CAS 67-56-1)	STEL	325 mg/m3
		250 ppm
	TWA	260 mg/m3
		200 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
Methylene Chloride (CAS 75-09-2)	0.3 mg/l	Dichloromethane	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1)

Skin designation applies.

Toluene (CAS 108-88-3)

Skin designation applies.

US - Tennessee OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Avoid exposure - obtain special instructions before use. Wear tight-fitting goggles or face shield. Wear safety glasses with side shields (or goggles). Avoid contact with eyes.

Hand protection

Avoid exposure - obtain special instructions before use. Wear appropriate chemical resistant gloves.

Skin protection

Other

Avoid exposure - obtain special instructions before use. Avoid contact with the skin. Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious apron is recommended. It may provide little or no thermal protection.

Skin protection

Respiratory protection

Avoid exposure - obtain special instructions before use. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Do not get in eyes. When using, do not eat, drink or smoke. Do not get this material in contact with skin. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Gas.

Form

Aerosol.

Color

Not available.

Odor

Not available.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

Not available.

Flash point

-156.0 °F (-104.4 °C) PROPELLANT estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1.9 % estimated

Flammability limit - upper (%) 9.5 % estimated

Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of explosion. Risk of ignition. Unstable. Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Inhalation	Harmful if inhaled. May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Dizziness. Nausea. Aspiration may cause pulmonary edema and pneumonitis. Irritation of eyes and mucous membranes. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful if inhaled.

Product	Species	Test Results
RAZOR (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rat	64601 mg/kg
<i>Inhalation</i>		
LC50	Rat	117 mg/l/4h
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l

Components	Species	Test Results
Methanol (CAS 67-56-1)		
Acute		
<i>Inhalation</i>		
LC50	Cat	85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours
	Mouse	79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours 82.1 mg/l, 6 Hours
<i>Oral</i>		
LD50	Monkey	6000 mg/kg
	Rat	1187 - 2769 mg/kg
<i>Other</i>		
LD50	Mouse	6000 mg/kg
Methylene Chloride (CAS 75-09-2)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg, Days
<i>Inhalation</i>		
LC50	Mouse	49 mg/l, 7 Hours
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h
Propylene Oxide (CAS 75-56-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	950 - 1250 mg/kg, 4 Hours 1.5 ml/kg, 4 Hours
<i>Inhalation</i>		
LC50	-	4197 ppm, 4 Hours 4124 mg/m3, 4 Hours
<i>Oral</i>		
LD50	Rat	382 - 587 mg/kg
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours 12.5 - 28.8 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation	Harmful in contact with eyes. Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	Irritating to skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Hazardous by OSHA criteria. Hazardous by WHMIS criteria. Cancer hazard.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Methylene Chloride (CAS 75-09-2)	2B Possibly carcinogenic to humans.
Propylene Oxide (CAS 75-56-9)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Methylene Chloride (CAS 75-09-2)	Cancer
US. National Toxicology Program (NTP) Report on Carcinogens	
Methylene Chloride (CAS 75-09-2)	Reasonably Anticipated to be a Human Carcinogen.
Propylene Oxide (CAS 75-56-9)	Reasonably Anticipated to be a Human Carcinogen.
Reproductive toxicity	Hazardous by OSHA criteria. Avoid exposure to women during early pregnancy. Possible reproductive hazard. Potential embryo-fetal toxicity and teratogenicity. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	May cause damage to organs.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Hazardous by WHMIS criteria. Hazardous by OSHA criteria. Prolonged or repeated exposure may cause lung injury. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects. Danger of serious damage to health by prolonged exposure. May cause damage to organs through prolonged or repeated exposure.
Further information	Reproductive toxicity. Danger of very serious irreversible effects. Symptoms may be delayed.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product	Species		Test Results
RAZOR (CAS Mixture)			
Aquatic			
Algae	IC50	Algae	741 mg/L, 72 Hours
Crustacea	EC50	Daphnia	82.4559 mg/L, 48 Hours
Fish	LC50	Fish	153 mg/L, 96 Hours
Components			
Methanol (CAS 67-56-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Methylene Chloride (CAS 75-09-2)			
Aquatic			
Algae	IC50	Algae	500.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1689.5 mg/L, 48 Hours
		Water flea (Daphnia magna)	1250 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	140.8 - 277.8 mg/l, 96 hours

Components	Species		Test Results
Propylene Oxide (CAS 75-56-9)			
Aquatic			
Crustacea	EC50	Daphnia	350 mg/L, 48 Hours
Toluene (CAS 108-88-3)			
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Butane	2.89
Methanol	-0.77
Methylene Chloride	1.25
Propane	2.36
Propylene Oxide	0.03
Toluene	2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Methanol (CAS 67-56-1)	U154
Methylene Chloride (CAS 75-09-2)	U080
Toluene (CAS 108-88-3)	U220

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82

Packaging exceptions 306

Packaging non bulk None

Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Packing group Not applicable.

Environmental hazards No.

ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed.

Cargo aircraft only Allowed.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950

UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) None

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT





15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Methanol (CAS 67-56-1)	Listed.
Methylene Chloride (CAS 75-09-2)	Listed.
Propylene Oxide (CAS 75-56-9)	Listed.
Toluene (CAS 108-88-3)	Listed.

SARA 304 Emergency release notification

Propylene Oxide (CAS 75-56-9)	100 LBS
-------------------------------	---------

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Methylene Chloride (CAS 75-09-2)	Cancer Heart Central nervous system Liver Skin irritation Eye irritation
----------------------------------	---

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No
--------------------------	---

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
---------------	------------	---------------------	-----------------------------	--	--

Propylene Oxide	75-56-9	100	10000 lbs		
-----------------	---------	-----	-----------	--	--

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methylene Chloride	75-09-2	60 - 80
Methanol	67-56-1	2.5 - 10
Toluene	108-88-3	2.5 - 10
Propylene Oxide	75-56-9	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

US. Rhode Island RTK

Butane (CAS 106-97-8)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Methylene Chloride (CAS 75-09-2) Listed: April 1, 1988
Propylene Oxide (CAS 75-56-9) Listed: October 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012
Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-15-2015

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.