



K107 ALUMI-SHIELD

Aluminum Fibrated Roof Coating

Roofing

Alumi-Shield is a professional grade reflective coating containing 2lbs of high quality aluminum paste per gallon in a non-asbestos fibered asphalt base. The high concentration of aluminum paste in this coating make it a long lasting and highly reflective coating. This aluminum coating will serve as a weatherproof barrier as it reflects the sun's damaging rays. This will prolong the roof surface over which it is applied, and keep the building cooler in the summer. **Alumi-Shield** can be applied over asphalt, felts, composition, or metal surfaces.

USES:

Alumi-Shield is excellent for coating metal roofs, silos, barns, felts, built up asphalt roofs, and smooth surface SBS modified roll roofing.

PREPARATION:

Surfaces to be coated must be clean and dry. Remove all dirt, dust, debris, or other foreign matter by using a stiff brush, forced air, or hosing off the roof. Remove rust with a wire brush. If using on metal roofs, securely attach any loose panels before using **Alumi-Shield**. If applying over built up asphalt roofs, repair all splits, cracks, or blisters with Kayline **Dura-Patch**. Allow roof cement to dry thoroughly before applying aluminum coating.

COVERAGE:

Approximately 1.5 gallons per 100 sqft. on metal or single ply roofing, and 2 to 3 gallons per 100 sqft. on asphalt, felts, or composition roofing. If this coating is applied too thick it can crack and dry brown or with brown streaks or spots.