

K147 T-Ease

Dry Teflon Lubricant



T-EASE is a chemically inert, non-oily, non-staining lubricant and release agent that is clean and dry during use. The extremely slick nature of this waxy fluorocarbon will not dissolve away from surfaces and will not melt below 500°F. **T-EASE** repels oil and water, will not attract or hold dust or dirt, and will not become gummy. **T-EASE** is suitable for use as a release agent for rubber, epoxy, phenolic, polyester and other resins.

An excellent dry coating lubricant for saw blades, router bits, drill bits, sharpeners, planers, table tops, etc. Reduces friction, inhibits resin build-up and prolongs tool life.

Directions: SHAKE WELL BEFORE USING. Spray a light thin coat from a distance of approximately 6 inches. Paintable and contains no silicone or oil. Will not affect wood finish. **For best results**, make sure area is free of oil or grease residue by cleaning with Kayline's **BRUTE** degreaser and allow to dry. Hold container 5-10 inches from surface and spray area with a thin film.

Health	3
Flammability	4
Physical Hazard	0
Protection	X

Areas of Use:

- *Conveyors
- *Bottling Plants
- *HVAC dampers
- *Municipalities
- *Apartments
- *Rollers
- *Window and door tracks
- *Freezer compartments
- *Hinges

Appearance and odor.....	Gas/Aerosol
Specific Gravity.....	N/A
VOC%.....	N/A
Net Wt.	10 oz.

DISTRIBUTED BY:

KAYLINE COMPANY, PO BOX 603207, CLEVELAND, OHIO 44103 (216) 566-9858 (800) 426-5820 FAX (216) 566-1228

www.kaylinecompany.com