



K151 QUICK PATCH

Expansion Cement

Flooring

Quick Patch when mixed with water forms a high strength, 30 minute dry cement. It bonds quickly to existing cement floors, stairs, walls, pre-cast beams and columns. Withstands high impact loads, vibration and water erosion. **Quick Patch** expands for excellent grip upon curing and is very strong (compression strength: 1 hour -4358 psi; 7 days-8032 psi). Use to set bolts, anchors or rods in cement or concrete; grout walls and floors in pre-cast structures. Excellent freezer compartment floor repair material (Color: Gray)

USES:

Setting Machinery & Equipment Bolts,
Anchoring Re-Bars & Dowels,
Setting Sleeves, Setting Posts,
Grouting & Leveling Equipment,
Patching Holes & Cracks -
Vertical & Horizontal

FEATURES:

- * Fast - 30 Minute Set; Hard In 60 Minutes
- * Easy - No Heating Required
- * Fool Proof - Add Only Water; Any Water Supply Will Work
- * Practical - Wet Or Damp Concrete Is Suitable As Well As Dry
- * Universal - Temperature Doesn't Effect Set As Long As Settings Are Made Above Freezing Point Of Water
- * Economical - No Need To Apply Curing Compounds Or Special Additives
- * Special - This Cement Is Safe For Aluminum Setting
- * **Quick Patch** Is Not Highly Alkaline & Will Not Corrode Aluminum Metal