



K198 URETHANE CONCRETE SEAL

40% Seal For Concrete or Wood Floors

Flooring

An economical oil modified urethane concrete sealer designed to combine full gloss with tough durability. Outstanding leveling characteristics produce a uniform film that is highly resistant to chemicals, abrasion and is unsurpassed for resistance to rubber burns. Easily applied - ready to use, no mixing, provides a hard, long lasting finish.

RECOMMENDED USE:

First Coat:

300-400 sq./ft. per gallon

Additional Coats:

400-500 sq./ft. per gallon

To Touch:

2 hours

Hard:

4-8 hours

FEATURES:

- * Prevents Dusting, Crumbling, & Erosion Of Concrete
- * Extends Floor Life - High Abrasion & Impact Resistance
- * Excellent Resistance To Alcohol, Alkali, Fumes, Gases, Grease, Oil, Gasoline, Ink, Citrus Juices, Cleaning Chemicals, Moisture & Rubber Burns
- * Reduces Down Time - Area Can Be Opened For Traffic 24 Hours After Final Coat
- * Extra Light Color Will Not Discolor Floor Or Yellow With Age
- * High Gloss For Increased Light Reflection
- * Cuts Maintenance Costs - Prevents Soil Penetration So Cleanup Is Fast & Thorough
- * 40% Solid Contents