



T60 RED EXTREME PRESSURE NON-MELT GREASE

Excellent Extreme Pressure Grease, Particularly Where Bearings & Chassis Points Are Subject To Wet Or High Temperature Conditions Or Heavy Loads

- Excellent Shear Stability
- High Temperature Protection Up To 500°F
- Excellent Load Carrying Capacity - 65 Timken Load
 - Extreme Pressure Protection
- Resistant To Oxidation, Acids, Water, Salt Spray, Weather, Dirt, Dust & Steam
 - Contains Special Corrosion & Rust Inhibitors
- Exceptional Anti-Wear Properties, Even At High Temperatures
 - Excellent Adhesive & Cohesive Properties

DIRECTIONS

On First Application, Force Sufficient Grease Through The Bearing Or Fitting To Flush Out All The Old Grease & Contaminants.

Where Possible, Wash Out All Old Grease Entirely, & Replace With **RED GREASE** For Maximum Protection.

Net Wt. 14oz (396 Grams)

CAUTION:

Do Not Take Internally.
May Be Harmful If Swallowed.
For Eye Contact, Flush With Plenty
Of Water Until Irritation Subsides.
For Skin Contact, Wash With Soap & Water.

KEEP OUT OF REACH OF CHILDREN

GENERAL SPECIFICATIONS:

NLGI GRADE	2
Dropping Point	500°F
Timken Load	65
Corrosion Resistance	Excellent
Color	Dark Red



KAYLINE COMPANY, PO BOX 603207, CLEVELAND, OHIO 44103 (216) 566-9858 (800)426-5820 FAX (216)566-1228

www.kaylinecompany.com