Section 1 ~ Identification				
Identity (As Used On Label and List)	Date Prepared:			
A1286 FASTER	01-22-2021			
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300			
Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1	Telephone Number for Information: 1-800-571-7347			
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.			

Section 2 ~ Hazard(s) Identification

Classification Dissolved Gas Skin Irritant: Category 2

Skin Sensitization: Category 1

Specific Target Organ Toxicity (Single Exposure): Category 3

Carcinogenicity: Category 2

Aspiration Hazard

Hazard Statement(s)

DANGER: Contains gas under pressure; May explode if heated. Causes skin irritation. May cause respiratory irritation, drowsiness or

dizziness. Suspected of causing cancer. May be fatal if swallowed and enters airways. May cause an allergic skin reaction.

Precautionary Statements

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves/clothing and eye/face protection. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do

NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

Symbols







Hazards Not Otherwise Classified:

N/A

Section 3 ~ Composition/Information on Ingredients

Hazardous Ingredient	CAS No.	%(Wt.)
Carbon Dioxide	124-38-9	1 – 5%
Tetrachloroethylene	127-18-4	60 – 85%
Mineral Seal Oil	64741-44-2	5 – 10%

Section 4 ~ First Aid Measures

Eyes: Remove contact lenses. Flush with water for at least 15 minutes. See a physician if irritation persists.

Ingestion: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention.

Inhalation: Move to fresh air. If breathing is difficult, administer oxygen. Seek immediate medical attention.

Skin: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation persists.

Acute Health Hazards: Eyes: redness, tearing, blurred vision

Skin: Defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: Abdominal irritation, nausea, vomiting, and diarrhea. Aspiration risk.

Chronic Health Hazards: Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, lungs, blood, or central nervous systems. May cause dizziness, headache, nausea, mental confusion, or visual disturbances.

Note to Physician: Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

Section 5 ~ Fire Fighting Measures

Extinguishing Media: Dry chemical, foam, or Carbon Dioxide (CO2).

Unsuitable Extinguishing Media: Water spray/stream.

Special Fire Fighting Procedures: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

Unusual Fire and Explosion Hazards: Contents under pressure. Exposure to temperatures above 120°F may cause bursting.

Hazardous Combustion Products: Oxides of carbon, chlorine, hydrogen chloride and phosgene

Section 6 ~ Accidental Release Measures

Personal Protective Equipment: Refer to section 8 for proper Personal Protective Equipment.

Spill: Use absorbent on spill, sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.

Waste Disposal: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA Status: Waste solvent likely considered U210 (Tetrachloroethylene) under RCRA, however product should be fully characterized prior to disposal (40 CFR 261)

Section 7 ~ Handling and Storage

Handling and Storage: Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F.

Other Precautions: Keep out of the reach of children.

Incompatibility: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

Section 8 ~ Exposure Controls/Personal Protection

Hazardous Ingredient	OSHA PEL	ACGIH TLV	
Carbon Dioxide	5000 ppm	5000 ppm	
Tetrachloroethylene	100 ppm	25 ppm	
Mineral Seal Oil	5 mg/m3	200 mg/m3	

Engineering Controls / Ventilation: Material is heavier than air. Material may concentrate in low lying areas. Normal, forced ventilation required to meet TLV requirements. Local exhaust ventilation is generally preferred.

Respiratory Protection: Wear NIOSH/MSHA approved organic vapor respiratory protection if used in confined, poorly ventilated areas.

Personal Protective Equipment: Safety glasses, gloves and synthetic apron.

Additional Measures: Wash hands thoroughly after handling.

Section 9 ~ Physical Chemical Properties

Appearance: Clear, Yellow Aerosol Spray

Odor: Chlorinated solvent odor Odor Threshold: N/D Boiling Point: >188°F (87°C) Melting Point/Freezing Point: N/D

Flammability(solid gas): Not considered a flammable aerosol or an extremely flammable

aerosol by OSHA (29CFR 1910.1200)

Flash Point: N/D

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D UPPER FLAMMABILITY LIMIT: N/D EXPLOSIVE LIMIT LOWER (%): N/D EXPLOISVE LIMIT UPPER (%): N/D

Vapor Pressure (mm Hg): N/D Vapor Density (AIR=1): N/D Evaporation Rate: N/D

Relative Gravity (H2O=1): 1.40 - 1.55 @ 77°F (25°C)

Solubility (IES) 0%

Partition Coefficient: n-OCTANOL/WATER (KOW): N/D

Volatile Organic Compounds (VOC): 0% Autoignition Temperature: N/D Decomposition Temperature: N/D

Viscosity: N/D

Section 10 ~ Stability and Reactivity

Reactivity: Chemically active metals and bases

Chemical Stability: Stable

Conditions to Avoid: Temperatures greater than 122°F may cause bursting.

Incompatibility: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

Hazardous Decomposition or By-Product: Oxides of carbon, chlorine, hydrogen chloride and phosgene.

Possible Hazardous Reactions: None Known

Section 11 ~ Toxicological Information

Toxicological Information: Tetrachloroethylene (127-18-4) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mineral Seal Oil (64741-44-2) LD50 (Oral, Rat) 2629 mg/kg; LC50 (Inhalation, Mouse, 8hr) 34200 mg/m3 Mg/m

Rat) 5000 mg/kg; LD50 (Dermal, Rabbit) 2000 mg/kg Routes of Entry: Eyes, Ingestion, Inhalation, Skin

Eyes: Causes severe irritation, redness, tearing, pain, visual disturbance, may cause eye damage.

Ingestion: Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomiting, abdominal cramps.

Inhalation: Irritation to respiratory tract, dizziness, headache, nausea, depression of central nervous system, prolonged exposure may cause unconsciousness, heart effects, liver effects, kidney effects, and death.

Skin: Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.

Medical Condition Aggravated: Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central

Acute Health Hazards: Eyes: redness, tearing, blurred vision

Skin: Defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: Abdominal irritation, nausea, vomiting, and diarrhea. Aspiration risk.

Chronic Health Hazards: Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, lungs, blood, or central nervous systems. May cause dizziness, headache, nausea, mental confusion, or visual disturbances.

OSHA: Yes ACGIH: A2 - Suspected NTP: 2 - Anticipated IARC: 2A - Probable OTHER: CA Prop 65 Carcinogenicity:

Section 12 ~ Ecological Information

Ecological Information: Not Established.

Biodegradability: Component or components of this product are not biodegradable. Bioaccumulation: Components in this mixture can bioaccumulate in aquatic organisms.

Soil Mobility: This product is mobile in soil.

Other Ecological Hazards: This material is toxic to aquatic life.

Section 13 ~ Disposal Considerations

Waste Disposal: Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA Status: Waste solvent likely considered U210 (Tetrachloroethylene) under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Section 14 ~ Transportation Information

Proper Shipping Name: Aerosols, Ltd. Qty. Air Shipment Shipping by Water: Vessel (IMO/IMDG) Hazard Class/Division: 2.2 (6.1) Proper Shipping Name: Aerosols, Non-Flammable, Toxic, Proper Shipping Name: Aerosols, Toxic Hazard Class/Division: 2.2 (6.1) UN/NA Number: UN 1950 Containing Substances in Division 6.1 Packaging Group III Packaging Group: N/A Hazard Class/Division: 2.2 (6.1) UN/NA Number: UN 1950 UN/NA Number: UN 1950 Packaging Group: N/A Packaging Group: N/A Environmental Hazards Water: Marine Pollutant

Section 15 ~ Regulatory Information

TSCA Status: All Chemicals are listed or exempt.

CERCLA (Comprehensive Response Compensation, and Liability Act): Tetrachloroethylene (127-18-4) Reportable Quantity = 100 lbs

SARA 311/312 Hazard Categories: Acute Health, Chronic Health. SARA 313 Reportable Ingredients: Tetrachloroethylene (127-18-4)

State Regulations: Tetrachloroethylene (127-18-4) CA Prop 65: Chemical known to the state of California to cause cancer.

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	2	2	4= Severe
FLAMMABILITY	1	1	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	-	C	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance. DISTRIBUTED BY