
Safety Data Sheet

SECTION I - PRODUCT IDENTIFICATION

Trade Name: **Diamite SL Epoxy Flooring – Activator**
Product Code: 1050477 / 1060477
Manufacturer: Metalcrete Industries
4133 Payne Avenue
Cleveland, Ohio 44103
Recommended Use: Self-Leveling, Heavy-Duty Industrial Flooring
Telephone: 1-440-526-5600
Emergency Phone: 1-800-728-2482

SECTION 2 – HAZARDS IDENTIFICATION

Physical hazards: Not classified.
Health hazards: Skin Corrosion / Irritation Category 1
Skin Sensitizer Category 1B
Serious Eye Damage Category 1
Acute Hazard to Aquatics Category 3
Chronic Hazard to Aquatics Category 2

Label elements:



Signal word: Danger
Hazard statement: Causes severe skin burns and eye damage. May cause an allergic skin reaction.
Causes serious eye damage. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statements:

Prevention: Keep out of reach of children. Read label before use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection to prevent skin contact. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If on skin: Wash with plenty of soap and water. If skin irritation or burns develop: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes: Immediately call a poison center or doctor/physician. Collect spillage.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical Name	CAS Number	Percentage
Tetraethylene Pentamine	112-57-2	5.0 – 15.0
TOFA, Reaction Products with TEPA	68953-36-6	60.0 – 90.00

SECTION 4 – FIRST AID MEASURES

Eyes:	Flush eyes with water for at 15 minutes immediately after exposure. Contact a medical professional.
Ingestion:	Do not induce vomiting. Dilute by giving water or milk if victim is conscious. Contact a physician or poison control center immediately.
Inhalation:	Leave area to breathe fresh air if effects persist. Administer oxygen if necessary.
Skin:	Flush skin with soap and water. If skin unlikely irritation or rash develops, seek medical attention. Remove all contaminated clothing immediately. Get medical attention if redness or swelling occurs.

SECTION 5 – FIRE-FIGHTING MEASURES

Flash point:	200°F +
Autoignition temperature:	No information available.
Flammable limits in air - Lower (%):	No information available.
Flammable limits in air - Upper (%):	No information available.
Suitable extinguishing media:	Foam, alcohol foam, CO ₂ , and water fog.
Protective equipment for firefighters:	Protective clothing and approved breathing apparatus consistent with normal firefighting professionals and procedures.
Special firefighting procedures:	Toxic fumes will be evolved when this material is involved in a fire.
Unusual fire hazards:	No unusual fire hazards known.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Avoid spilling the material. Upon a liquid spill, dike the spill by using an inert absorbent material. Sweep up and transfer into an appropriate container for disposal. Dispose of this material in accordance with federal, state and local regulations. Flush the area with water to remove any excess residue.

SECTION 7 – HANDLING AND STORAGE

Material should be stored in a cool, dry location in a sealed container. After use, reseal partially used containers. Properly label all containers. When handling this material, avoid inhaling vapors and avoid contact with eyes and skin. Wash with soap and water before eating, drinking, or using the toilet. The use of respirators, goggles, and gloves are recommended protective handling equipment.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION EQUIPMENT

Eye protection:	Wear appropriate eye protection such as safety goggles or face shields. Avoid contact eyes and face while handling this material. If eyes become contaminated, use eye wash station.
Respiratory protection:	Wear appropriate NIOSH approved respirator as required to prevent over exposure to vapor in accordance with 29 CFR 1910.134.
Skin protection:	Wear impervious protective gloves. In addition to protecting hands, make sure suitable protective clothing is worn by material handlers to prevent skin irritation elsewhere on body.
Engineering Controls:	This material should be used in well ventilated areas. Mechanical and local exhausts should be used in poorly ventilated areas.

EXPOSURE LIMITS

Chemical Name	CAS Number	Regulation	Limit
Tetraethylene Pentamine	112-57-2	OSHA PEL ACGIH TLV	None None
TOFA, Reaction Products with TEPA	68953-36-6	OSHA STEL OSHA PEL ACGIH TLV OSHA STEL	None None None None

K150

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Color:	Amber
Odor:	Slight Amine
Boiling point or range:	155°F to 401°F
Vapor density:	No data available.
pH:	N/A
Specific gravity:	0.90
Solubility in water:	Negligible

SECTION 10 – STABILITY AND REACTIVITY

Stability:	This material is stable under recommended storage, usage, and handling procedures.
Conditions to avoid:	Avoid excess heat or open flames.
Materials to avoid:	Can react with strong oxidizing agents, strong acids, and mineral acids.
Hazardous decomposition:	CO ₂ , aldehydes, and acids. Reaction with some curing agents can generate large amounts of heat.
Hazardous polymerization:	Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL OVERVIEW

Diamite SL Epoxy Flooring – Activator is an amber liquid. Vapors may irritate eyes. Do not breathe in vapors. Use a respirator while using this product. If overexposed to vapors, leave the area immediately to breathe fresh air. Use gloves.

ACUTE HEALTH EFFECTS OF EXPOSURE & ROUTES OF EXPOSURE

Eyes:	Will cause burns to the eyes. High vapor concentrations can cause severe irritation to the eyes.
Ingestion:	This material can cause damage to mucous membranes if swallowed.
Inhalation:	High concentrations or vapor can cause irritation to the respiratory tract, nausea, and dizziness.
Skin:	This material may cause skin irritation or possible burns to the skin.
Exposure:	Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic responses.

SECTION 12 – ECOLOGICAL INFORMATION

No information available. Release of this product into surface waters or other natural ecosystems should be avoided.

SECTION 13 – DISPOSAL CONSIDERATION

K150

Material disposal method: Disposal of this material should comply with federal, state, and local regulations for hazardous waste. Do not discharge into drains or groundwater runoff.

Container disposal method: Disposal of this material's packaging should comply with federal, state, and local regulations.

SECTION 14 – TRANSPORT INFORMATION

USDOT: NOT REGULATED

NMFC: Class 55

Commodity: Paint Materials
UN3082, Environmentally Hazardous Substance, Liquid, N.O.S. (Contains Bisphenol A Diglycidyl Ether Polymer) , 9, PGIII

SECTION 15 – REGULATORY INFORMATION

FEDERAL REGULATIONS

SARA 313: This product contains no chemicals that are subject to Annual Release Reporting Requirements under SARA Section 313 (40 CFR 372)

TSCA Registration: All components are either listed or exempt from the Toxic Substance Control Act inventory.

OSHA Regulations: This product is not a substance specifically regulated by OSHA (29 CFR 1910.1001-1050). No listed raw materials for this product are regulated as carcinogens.

This product contains "Hazardous Chemicals" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Chemical Name	CAS Number	Hazard Information
Tetraethylene Pentamine	112-57-2	OSHA - Irritant
TOFA, Reaction Products with TEPA	68953-36-6	Harmful if inhaled or swallowed

SECTION 16 – OTHER INFORMATION

HMIS Rating	
Health	2
Flammability	1
Physical Hazard	0

0 = Essentially no danger
1 = Slight danger
2 = Moderate danger
3 = Serious danger
4 = Extreme danger

Further consideration: Some components of Diamite SL Epoxy Flooring – Activator are considered hazardous by OSHA's Standards but Diamite SL Epoxy Flooring – Activator is generally considered a safe material for routine use. When Diamite SL Epoxy Flooring – Activator is used responsibly it is not considered a dangerous material. Diamite SL Epoxy Flooring – Activator is used in bridges, buildings, and other infrastructure around the world that we intimately use every day.

Metalcrete Industries believes the information contained within this Safety Data Sheet to be accurate and reliable as of the date of preparation, or is obtained from sources believed to be accurate. Metalcrete Industries gives no warranty expressed or implied as to the accuracy of the information contained herein and assume no responsibility for damage to any person, property, or business arising from use of this material. Hazard information stated within this document is provided in good faith, is for the consideration of the user, and is subject to the user's own investigation of compliance with acceptable regulations. It is the sole responsibility of the purchaser or user of this product to ensure that it is properly and safely used.

Safety Data Sheet

SECTION I - PRODUCT IDENTIFICATION

Trade Name: **Diamite SL Epoxy Flooring – Aggregate**
Product Code: 8060058
Manufacturer: Metalcrete Industries
4133 Payne Avenue
Cleveland, Ohio 44103
Recommended Use: Aggregate for Epoxy Flooring
Telephone: 1-440-526-5600
Emergency Phone: 1-800-633-8253

SECTION 2 – HAZARDS IDENTIFICATION

Physical hazards: Not classified.
Health hazards: Mild Eye Irritation Category 2B
Carcinogenicity Category 1B
Target Organ Systemic Toxicity Category 3 Respiratory Irritation

Label elements:



Signal word: Danger
Hazard statement: Causes eye irritation. May cause respiratory irritation. May cause cancer. Causes damage to lungs through prolonged or repeated inhalation.

Precautionary statements:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: If exposed or concerned: Get medical advice/attention. If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Storage: Store in a cool, well-ventilated place. Store in a dry place in a closed container.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3 – PRODUCT COMPOSITION

K150

Chemical Name	CAS Number	Percentage
Crystalline Silica	14808-60-7	95.0 – 99.0
Fine Aggregates	Not Regulated	< 5.0

SECTION 4 – FIRST AID MEASURES

Eyes:	Flush eyes with water for at 15 minutes immediately after exposure. Contact a medical professional.
Ingestion:	Do not induce vomiting. If ingested, contact a physician or poison control center immediately.
Inhalation:	Leave area to avoid dust and breathe fresh air. Seek medical attention is respiratory irritation persists.
Skin:	Wash skin with soap and water. If skin irritation or rash develops, seek medical attention.

SECTION 5 – FIRE-FIGHTING MEASURES

Flash point:	No information available.
Autoignition temperature:	No information available.
Flammable limits in air - Lower (%):	No information available.
Flammable limits in air - Upper (%):	No information available.
Suitable extinguishing media:	This material is non-combustible. Use extinguishing media appropriate to the surrounding area.
Protective equipment for firefighters:	Protective clothing and approved breathing apparatus consistent with normal firefighting professionals and procedures.
Firefighting measures:	This material is not expected to burn.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Avoid creating excessive dust. Dampen material with water to control dusting. Sweep up and transfer into an appropriate container for disposal. Dispose of this material in accordance with federal, state and local regulations.

SECTION 7 – HANDLING AND STORAGE

Material should be stored in a cool, dry location in a sealed container. When handling this material, avoid inhaling dust and avoid contact with eyes and skin. The use of respirators, goggles, and gloves are recommended protective handling equipment.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION EQUIPMENT

Eye protection:	Wear appropriate eye protection such as safety goggles or face shields. Avoid contact eyes and face while handling this material. If eyes become contaminated, use eye wash station.
Respiratory protection:	Wear appropriate NIOSH approved dust respirator when airborne dust levels exceed threshold limit value as indicated on manufacturer's SDS.
Skin protection:	Wear impervious protective gloves. In addition to protecting hands, make sure suitable protective clothing is worn by material handlers to prevent skin irritation elsewhere on body.
Engineering Controls:	This material should be used in well ventilated areas. Mechanical and local exhausts should be used in poorly ventilated areas.

EXPOSURE LIMITS

K150

Chemical Name	CAS Number	Regulation	Limit
Crystalline Silica	14808-60-7	OSHA TWA	0.1 mg/m ³ Respirable
		OSHA TWA	0.3 mg/m ³ Total Dust
		ACGIH TWA	0.025 mg/m ³ Repirable Fraction

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Form:	Granular
Color:	Beige
Odor:	Odorless
pH:	No information available.
Specific gravity:	2.65
Solubility in water:	No information available.

SECTION 10 – STABILITY AND REACTIVITY

Stability:	This material is stable under recommended storage, usage, and handling procedures.
Hazardous Reactions:	Will not occur under normal conditions.
Non-Hazardous Reactions:	No information available.

SECTION 11 – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL OVERVIEW

Diamite SL Epoxy Flooring – Aggregate is a beige granular material. Dust in air may irritate respiratory tract and eyes. Do not breathe in dust. Use a respirator while using this product. If overexposed to dust, leave the area immediately to breathe fresh air.

ACUTE HEALTH EFFECTS OF EXPOSURE & ROUTES OF EXPOSURE

Eyes:	Dust may cause eye irritation and abrasion. Flush eyes with water immediately after. Exposure to avoid irritation and possible chemical burns.
Ingestion:	Digesting this material may cause irritation to the mouth, throat, and digestive tract. If ingested, contact your primary care physician immediately.
Inhalation:	Do not breathe in dust. Dust may irritate nose, mouth, and respiratory tract.
Skin:	This material may cause skin irritation.

CHRONIC HEALTH EFFECTS OF EXPOSURE

Prolonged and repeated exposure to free crystalline silica quartz has been evaluated by IARC as having sufficient evidence of producing cancer in laboratory animals and humans (Group 1). Silicosis may result from breathing in free silica. Avoid prolonged and repeated exposure to this material.

SECTION 12 – ECOLOGICAL INFORMATION

This product is not expected to be hazardous to the environment; however release of this product into surface waters or other natural ecosystems should be avoided.

SECTION 13 – DISPOSAL CONSIDERATION

K150

Material disposal method: Disposal of this material should comply with federal, state, and local regulations. Do not discharge into drains or groundwater runoff.

Container disposal method: Disposal of this material's packaging should comply with federal, state, and local regulations.

SECTION 14 – TRANSPORT INFORMATION

USDOT: NOT REGULATED, NON-HAZARDOUS

NMFC: Class 50

Commodity: Natural Aggregate

SECTION 15 – REGULATORY INFORMATION

FEDERAL REGULATIONS

SARA 311/312: Hazard Categories for SARA 311/312 Reporting: Yes

SARA 313: This product contains no chemicals that are subject to Annual Release Reporting Requirements under SARA Section 313 (40 CFR 372)

TSCA Registration: All components are either listed or exempt from the Toxic Substance Control Act inventory.

OSHA Regulations: This product is not a substance specifically regulated by OSHA (29 CFR 1910.1001-1050). This product contains "Hazardous Chemicals" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

STATE REGULATIONS

State RTK	Chemical Name	CAS Number
MA, NJ, PA	Crystalline Silica	14808-60-7

CA PROPOSITION 65: This material contains chemicals to cause cancer, birth defects, and/or other reproductive harm.

SECTION 16 – OTHER INFORMATION

HMIS Rating	
Health	1
Flammability	0
Physical Hazard	0

0 = Essentially no danger

1 = Slight danger

2 = Moderate danger

3 = Serious danger

4 = Extreme danger

Further consideration: Some components of Diamite SL Epoxy Flooring – Aggregate are considered hazardous by OSHA's Standards but Diamite SL Epoxy Flooring – Aggregate is generally considered a safe material for routine use. When Diamite SL Epoxy Flooring – Aggregate is used responsibly it is not considered a dangerous material. Components of Diamite SL Epoxy Flooring – Aggregate are used to make concrete floors, roads, bridges, buildings, and other infrastructure around the world that we intimately use every day.

Metalcrete Industries believes the information contained within this Safety Data Sheet to be accurate and reliable as of the date of preparation, or is obtained from sources believed to be accurate. Metalcrete Industries gives no warranty expressed or implied as to the accuracy of the information contained herein and assume no responsibility for damage to any person, property, or business arising from use of this material. Hazard information stated within this document is provided in good faith, is for the consideration of the user, and is subject to the user's own investigation of compliance with acceptable regulations. It is the sole responsibility of the purchaser or user of this product to ensure that it is properly and safely used.

Distributed By:

Safety Data Sheet

SECTION I - PRODUCT IDENTIFICATION

Trade Name: **Diamite SL Epoxy Flooring – Binder**
Product Code: 1050477 / 1060477
Manufacturer: Metalcrete Industries
4133 Payne Avenue
Cleveland, Ohio 44103
Recommended Use: Self-Leveling, Heavy-Duty Industrial Flooring
Telephone: 1-440-526-5600
Emergency Phone: 1-800-633-8253

SECTION 2 – HAZARDS IDENTIFICATION

Physical hazards: Not classified.
Health hazards: Serious Eye Damage/Irritation Category 2A
Skin Irritation Category 2
Skin Sensitizer Category 1
Long Term Hazards to Aquatics Category 2

Label elements:



Signal word: Warning
Hazard statement: Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

Precautionary statements:

Prevention: Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

Response: If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect spillage.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3 – PRODUCT COMPOSITION

K150

Chemical Name	CAS Number	Percentage
Modified Diglycidyl Ether of Bisphenol A	25068-38-6	60.0 – 90.0
Alkyl Glycidyl Ether	68609-97-2	10.0 – 30.0
Siloxanes & Silicones	67762-90-7	< 1.0
Siloxanes & Silicones	63148-62-9	< 1.0

SECTION 4 – FIRST AID MEASURES

Eyes:	Flush eyes with water for at 15 minutes immediately after exposure. Contact a medical professional.
Ingestion:	Do not induce vomiting. If ingested, contact a physician or poison control center immediately.
Inhalation:	Leave area to breathe fresh air. Seek medical attention is respiratory irritation persists.
Skin:	Wash skin with soap and water. If skin unlikely irritation or rash develops, seek medical attention.

SECTION 5 – FIRE-FIGHTING MEASURES

Flash point:	200°F
Autoignition temperature:	No information available.
Flammable limits in air - Lower (%):	No information available.
Flammable limits in air - Upper (%):	No information available.
Suitable extinguishing media:	Foam, alcohol foam, CO ₂ , dry chemical, and water fog.
Protective equipment for firefighters:	Protective clothing and approved breathing apparatus consistent with normal firefighting professionals and procedures.
Unusual fire hazards:	No unusual fire hazards known.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Avoid spilling the material. Upon a liquid spill, dike the spill by using an inert absorbent material. Sweep up and transfer into an appropriate container for disposal. Dispose of this material in accordance with federal, state and local regulations. Flush the area with water to remove any excess residue.

SECTION 7 – HANDLING AND STORAGE

Material should be stored in a cool, dry location in a sealed container. When handling this material, avoid inhaling vapors and avoid contact with eyes and skin. Wash with soap and water before eating, drinking, or using the toilet. The use of respirators, goggles, and gloves are recommended protective handling equipment.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION EQUIPMENT

Eye protection:	Wear appropriate eye protection such as safety goggles or face shields. Avoid contact eyes and face while handling this material. If eyes become contaminated, use eye wash station.
Respiratory protection:	Wear appropriate NIOSH approved respirator as required to prevent over exposure to vapor in accordance with 29 CFR 1910.134.
Skin protection:	Wear impervious protective gloves. In addition to protecting hands, make sure suitable protective clothing is worn by material handlers to prevent skin irritation elsewhere on body.
Engineering Controls:	This material should be used in well ventilated areas. Mechanical and local exhausts should be used in poorly ventilated areas.

EXPOSURE LIMITS

Chemical Name	CAS Number	Regulation	Limit
Modified Diglycidyl Ether of Bisphenol A	25068-38-6	OSHA PEL	None
		ACGIH TLV	None
		OSHA STEL	None
Alkyl Glycidyl Ether	68609-97-2	OSHA PEL	None
		ACGIH TLV	None
		OSHA STEL	None
Siloxanes & Silicones	67762-90-7	OSHA PEL	None
		ACGIH TLV	None
		OSHA STEL	None
Siloxanes & Silicones	63148-62-9	OSHA PEL	None
		ACGIH TLV	None
		OSHA STEL	None

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Color:	Variety of colors
Odor:	Odorless
pH:	N/A
Specific gravity:	1.1
Solubility in water:	Negligible

SECTION 10 – STABILITY AND REACTIVITY

Stability:	This material is stable under recommended storage, usage, and handling procedures.
Conditions to avoid:	Avoid excess heat or open flames.
Materials to avoid:	Avoid strong oxidizing agents, strong acids, and mineral acids.
Hazardous decomposition:	Reaction with some curing agents can generate large amounts of heat.
Hazardous polymerization:	Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATIONTOXICOLOGICAL OVERVIEW

Diamite SL Epoxy Flooring – Binder is a colored liquid. Vapors may irritate eyes. Do not breathe in vapors. Use a respirator while using this product. If overexposed to vapors, leave the area immediately to breathe fresh air. Use gloves.

ACUTE HEALTH EFFECTS OF EXPOSURE & ROUTES OF EXPOSURE

Eyes:	May cause irritation but corneal injury is not likely.
Ingestion:	This material has a low oral toxicity. Ingesting this material may cause irritation to the digestive tract.
Inhalation:	Do not breathe in vapors. Heated vapors can cause irritation to the nose or throat.
Skin:	This material may cause skin irritation or may trigger an allergic reaction.

SECTION 12 – ECOLOGICAL INFORMATION

Component data:

CAS# 25068-38-6: Biodegradability 12%, Fish toxicity: Rainbow trout (96 hour) LC50 1.5 mg/l, Zebra Fish (96 hour) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24 hour) EC50 3.6 mg/l

SECTION 13 – DISPOSAL CONSIDERATION

K150

Material disposal method: Disposal of this material should comply with federal, state, and local regulations. Do not discharge into drains or groundwater runoff.

Container disposal method: Disposal of this material's packaging should comply with federal, state, and local regulations.

SECTION 14 – TRANSPORT INFORMATION

USDOT: NOT REGULATED, ENVIRONMENTALLY HAZARDOUS

NMFC: Class 55

Commodity: Paint Materials
UN3082, Environmentally Hazardous Substance, Liquid, N.O.S. (Contains Bisphenol A Diglycidyl Ether Polymer) , 9, PGIII, Marine Pollutant

SECTION 15 – REGULATORY INFORMATION

FEDERAL REGULATIONS

SARA 313: This product contains no chemicals that are subject to Annual Release Reporting Requirements under SARA Section 313 (40 CFR 372)

TSCA Registration: All components are either listed or exempt from the Toxic Substance Control Act inventory.

OSHA Regulations: This product is not a substance specifically regulated by OSHA (29 CFR 1910.1001-1050). This product contains "Hazardous Chemicals" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

STATE REGULATIONS

State RTK	Chemical Name	CAS Number
NJ, PA	Modified Diglycidyl Ether of Bisphenol A	25068-38-6
NJ, PA	Alkyl Glycidyl Ether	68609-97-2

SECTION 16 – OTHER INFORMATION

HMIS Rating	
Health	1
Flammability	1
Physical Hazard	0

0 = Essentially no danger
1 = Slight danger
2 = Moderate danger
3 = Serious danger
4 = Extreme danger

Further consideration: Some components of Diamite SL Epoxy Flooring – Binder are considered hazardous by OSHA's Standards but Diamite SL Epoxy Flooring – Binder is generally considered a safe material for routine use. When Diamite SL Epoxy Flooring – Binder is used responsibly it is not considered a dangerous material. Diamite SL Epoxy Flooring – Binder is used in bridges, buildings, and other infrastructure around the world that we intimately use every day.

Metalcrete Industries believes the information contained within this Safety Data Sheet to be accurate and reliable as of the date of preparation, or is obtained from sources believed to be accurate. Metalcrete Industries gives no warranty expressed or implied as to the accuracy of the information contained herein and assume no responsibility for damage to any person, property, or business arising from use of this material. Hazard information stated within this document is provided in good faith, is for the consideration of the user, and is subject to the user's own investigation of compliance with acceptable regulations. It is the sole responsibility of the purchaser or user of this product to ensure that it is properly and safely used.

Distributed By: