


This brief provides a general overview of the **Safety Data Sheet** requirements in the Hazard Communication Standard OSHA's 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200).

Section 1 ~ Identification

Identity (As Used On Label and List) A1028 BELT TITE	Date Prepared: 06-04-2015
Company Information: OMEGA INDUSTRIAL SUPPLY, INC	Emergency Telephone Number: 1-800-424-9300
Address (Number, Street, Suite/Apt#) 101 Grobric Ct #1	Telephone Number for Information: 1-800-571-7347
(City, State, and Zip Code) Fairfield, CA 94534	Signature of Prepare (Optional) REGULATORY DEPT.

Section 2 ~ Hazard(s) Identification

Physical Hazards	Flammable aerosols Skin corrosion/irritation Serious eye damage/eye irritation	Category 1 Category 2 Category 2A
Health Hazards	Germ cell mutagenicity Carcinogenicity Specific target organ toxicity, single exposure narcotic effects	Category 2 Category 1B Category 3
OSHA Defined Hazards	Not classified.	
Label Elements		Signal Word: Danger
Hazard Statement	Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing genetic defects. May cause cancer.	
Precautionary Statement Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.	
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) Not Otherwise Classified (HNOC)	Harmful to aquatic life. Harmful to aquatic life with long lasting effects.	Supplemental Information None

Section 3 ~ Composition/Information on Ingredients

Chemical Name	CAS No.	%(Wt.)
Butane	106-97-8	20 – 40
Trichloroethylene	79-01-6	20 – 40
Propane	74-98-6	10 – 20
Naphtha, Petroleum, Light Alkylate	64741-66-8	2.5 – 10
1,2-Butylene Oxide	106-88-7	0.1 – 1
Other components below reportable levels		10 – 20

* Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4 ~ First Aid Measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin Contact: Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion: In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most Important Symptoms/Effects, Acute And Delayed: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of Immediate Medical Attention And Special Treatment Needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General Information: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Section 5 ~ Fire Fighting Measures

Suitable Extinguishing Media: Powder. Carbon dioxide (CO2).
Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.
Specific Hazards Arising From The Chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special Protective Equipment And Precautions For Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire Fighting Equipment/Instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General Fire Hazards: Extremely flammable aerosol.

Section 6 ~ Accidental Release Measures

Personal Precautions, Protective Equipment And Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods And Materials For Containment And Cleaning Up: Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental Precautions: Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Section 7 ~ Handling and Storage

Precautions For Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Level 2 Aerosol.

Conditions For Safe Storage, Including Any Incompatibilities: Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 ~ Exposure Controls/Personal Protection

Occupational Exposure Limits:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			US. NIOSH: Pocket Guide to Chemical Hazards		
Components	Type	Value	Components	Type	Value
Propane (74-98-6)	PEL	1800 mg/m3 1000 ppm	Butane (106-97-8)	TWA	1900 mg/m3 800 ppm
US. OSHA Table Z-2 (29 CFR 1910.1000)			Propane (74-98-6)	TWA	1800 mg/m3 1000 ppm
Components	Type	Value	Trichloroethylene (79-01-6)	TWA	25 ppm
Trichloroethylene (79-01-6)	Ceiling	200 ppm			
	TWA	100 ppm	US. Workplace Environmental Exposure Level (WEEL) Guides		
US. ACGIH Threshold Limit Values			Components	Type	Value
Butane (106-97-8)	STEL	1000 ppm	1,2-Butylene Oxide (106-88-7)	TWA	5.9 mg/m3 2 ppm
Trichloroethylene (79-01-6)	STEL	25 ppm			
	TWA	10 ppm			

Biological Limit Values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Trichloroethylene (79-01-6)	15 mg/l	Trichloroacetic acid	Urine	*
	0.5 mg/l	Trichloroethanol, without hydrolysis	Blood	*

* - For sampling details, please see the source document.

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual Protection Measures, Such As Personal Protective Equipment

Eye/Face Protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other: Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 ~ Physical Chemical Properties

Physical State: Gas.

Form: Aerosol.

Color: Not available.

Odor: Not available.

Odor Threshold: Not available.

pH: Not available.

Melting Point/Freezing Point: Not available.

Initial Boiling Point And Boiling Range: 194 °F (90 °C) estimated

Flash Point: -156.0 °F (-104.4 °C) Propellant estimated

Evaporation Rate: Not available.

Flammability (solid, gas): Not available.

Upper/Lower Flammability Or Explosive Limits

Flammability limit – lower (%): 6.7 % estimated

Flammability limit – upper (%): 43.8 % estimated

Explosive limit - lower (%): Not available.

Explosive limit - upper (%): Not available.

Vapor Pressure: 45 - 55 psig @70F estimated

Vapor Density: Not available.

Relative Density: Not available.

Solubility (ies)

Solubility (water): Not available.

Partition Coefficient (n-octanol/water): Not available.

Auto-Ignition Temperature: 779.98 °F (415.55 °C) estimated

Decomposition Temperature: Not available.

Viscosity: Not available.

Other Information

Explosive Properties: Not explosive.

Oxidizing Properties: Not oxidizing.

Specific Gravity: 0.826 estimated

Section 10 ~ Stability and Reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Possibility Of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions To Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible Materials: Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous Decomposition Products: No hazardous decomposition products are known.

Section 11 ~ Toxicological Information

Information On Likely Routes Of Exposure

Inhalation: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Skin Contact: Causes skin irritation.

Eye Contact: Causes serious eye irritation.

Ingestion: Expected to be a low ingestion hazard.

Symptoms Related To The Physical, Chemical And Toxicological Characteristics: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information On Toxicological Effects

Acute Toxicity: Narcotic effects.

Components

1,2-Butylene Oxide (106-88-7)

Acute

Dermal LD50

Inhalation

Species

Rabbit

Test Results

1500 – 2950 mg/kg, 24 Hours

1.77 ml/kg, 24 Hours

Vapor LC 50	Rat	>6.3 mg/l
Oral LD50	Rat	1 – 1.58 mg/kg 1100 µl/kg 1.3 ml/kg
Butane (106-97-8)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52%, 120 Minutes 1355 mg/l

Naphtha, Petroleum, Light Alkylate (64741-66-8)

Acute		
Dermal LD50	Rabbit	>1900 mg/kg, 24 Hours
Inhalation LC50	Rat	>5000 mg/m3, 4 Hours >4980 mg/m3 >4980 mg/m3, 4 Hours >4.96 mg/l, 4 Hours
Oral LD50	Rat	4820 mg/kg

Propane (74-98-6)

Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes 52%, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

Trichloroethylene (79-01-6)

Acute		
Dermal LD50	Rat	19031 mg/kg
Inhalation LC50	Dog; Mouse; Rabbit; Rat	8450ppm, 4 Hours 12500 ppm, 4 Hours 1044 mg/l/4h
Oral LD50	Dog; Mouse; Rat	2900 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Eye Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization

Respiratory Sensitization: Not a respiratory sensitizer.

IARC Monographs. Overall Evaluation of Carcinogenicity: 1,2-Butylene Oxide (106-88-7)
Trichloroethylene (79-01-6)

Skin Sensitization: This product is not expected to cause skin sensitization.

Germ Cell Mutagenicity: Suspected of causing genetic defects.

Carcinogenicity: May cause cancer.

2B Possibly carcinogenic to humans.

If <1L: Consumer Commodity Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens: Trichloroethylene (79-01-6)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive Toxicity: This product is not expected to cause reproductive or developmental effects.

Specific Target Organ Toxicity - Single Exposure: May cause drowsiness and dizziness.

Specific Target Organ Toxicity - Repeated Exposure: Not classified.

Aspiration Hazard: Not likely, due to the form of the product.

Chronic Effects: Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Section 12 ~ Ecological Information

Ecotoxicity: Harmful to aquatic life with long lasting effects.

<u>Product</u>	<u>Species</u>	<u>Test Results</u>
Belt Tite		
Aquatic		
Crustacea	EC50 Daphnia	6.143 mg/L, 48 Hours estimated
Fish	LC50 Fish	144.4846 ppm, 96 hours estimated

<u>Components</u>	<u>Species</u>	<u>Test Results</u>
1,2-Butylene Oxide (106-88-7)		
Aquatic		
Algae	IC50 Algae	500 mg/L, 72 Hours
Crustacea	EC50 Daphnia	69.8 mg/L, 48 Hours
Fish	LC50 Fish	160, 96 Hours

Naphtha, Petroleum, Light Alkylate (64741-66-8)

Aquatic		
Algae	IC50 Algae	30000 mg/L, 72 Hours

Trichloroethylene (79-01-6)

Aquatic		
Crustacea	EC50 Daphnia	2.2 mg/L, 48 Hours
Fish	LC50 Fish	40.8933, 96 Hours
	Flagfish (Jordanella floridae)	3.1 mg/l, 96 Hours

* Estimates for product may be based on additional component data not shown.

Persistence And Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential

Partition coefficient n-octanol / water (log Kow)

Butane	2.89	Propane	2.36	Trichloroethylene	2.61
--------	------	---------	------	-------------------	------

Mobility In Soil: No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 ~ Disposal Considerations

Disposal Instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local Disposal Regulations: Dispose in accordance with all applicable regulations.

Hazardous Waste Code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from Residues / Unused Products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated Packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Section 14 ~ Transport Information

DOT UN Number: UN1950 UN Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity) Class: 2.1 Transport Hazard Class(es) Subsidiary Risk: 6.1(PGIII) Label(s): 2.1, 6.1 Packing Group: Not applicable. Special Provisions: N82 Packaging Exceptions: 306 Packaging Non Bulk: None Packaging Bulk: None	IATA UN Number: UN1950 UN Proper Shipping Name: Aerosols, flammable Transport Hazard Class(es) Class: 2.1 Subsidiary Risk: 6.1(PGIII) Label(s): 2.1, 6.1 Packing Group: Not applicable. Environmental Hazards: No. ERG Code: 10L Other Information Passenger and Cargo Aircraft: Allowed with restrictions. Cargo Aircraft Only: Allowed with restrictions. Packaging Exceptions: LTD QTY	IMDG UN Number: UN1950 UN Proper Shipping Name: AEROSOLS Class: 2.1 Transport Hazard Class(es) Subsidiary Risk: 6.1(PGIII) Label(s): 2.1, 6.1 Packing Group: Not applicable. Environmental Hazards Marine Pollutant: No. EmS: F-D, S-U Packaging Exceptions: LTD QTY Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.
---	--	---

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
 This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.



Section 15 ~ Regulatory Information

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)
 1,2-Butylene Oxide (106-88-7) Listed.
 Trichloroethylene (79-01-6) Listed.
SARA 304 Emergency Release Notification: Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.
Superfund Amendments and Reauthorization Act of 1986 (SARA)
Hazard Categories Immediate Hazard – Yes Delayed Hazard – Yes Fire Hazard - Yes
 Pressure Hazard – No Reactivity Hazard - No
SARA 302 Extremely Hazardous Substance: Not listed.
SARA 311/312 Hazardous Chemical: No
SARA 313 (TRI reporting)

Chemical Name	CAS Number	% By Wt.
Trichloroethylene	79-01-6	20 - 40
1,2-Butylene Oxide	106-88-7	0.1 - 1

Other Federal Regulations
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List
 1,2-Butylene Oxide (CAS 106-88-7) Trichloroethylene (CAS 79-01-6)
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
 Butane (CAS 106-97-8) Propane (CAS 74-98-6)
Safe Drinking Water Act (SDWA): Not regulated.
US State Regulations
US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.
US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))
 1,2-Butylene Oxide (CAS 106-88-7) Butane (CAS 106-97-8)
 Naphtha, Petroleum, Light Alkylate (CAS 64741-66-8) Trichloroethylene (CAS 79-01-6)

US. Massachusetts RTK - Substance List	US. New Jersey Worker and Community Right-to-Know Act	US. Pennsylvania Worker and Community Right-to-Know Law	US. Rhode Island RTK
1,2-Butylene Oxide (106-88-7)	1,2-Butylene Oxide (106-88-7)	1,2-Butylene Oxide (106-88-7)	1,2-Butylene Oxide (106-88-7)
Butane (106-97-8)	Butane (106-97-8)	Butane (106-97-8)	Butane (106-97-8)
Propane (74-98-6)	Propane (74-98-6)	Propane (74-98-6)	Propane (74-98-6)
Trichloroethylene (79-01-6)	Trichloroethylene (79-01-6)	Trichloroethylene (79-01-6)	Trichloroethylene (79-01-6)

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.
US - California Proposition 65 - CRT: Listed date/Carcinogenic Substance: Trichloroethylene (79-01-6) Listed: April 1, 1988
US - California Proposition 65 - CRT: Listed date/Developmental Toxin: Trichloroethylene (79-01-6) Listed: Jan 31, 2014
US - California Proposition 65 - CRT: Listed date/Male Reproductive Toxin: Trichloroethylene (79-01-6) Listed: Jan 31, 2014

US State Regulations
International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 ~ Other Information

	NFPA	HMIS	Key
HEALTH	3*	3*	4= Severe
FLAMMABILITY	3	3	3= Serious
REACTIVITY	0	0	2= Moderate
OTHER/PROTECTION	-	X	1= Slight
			0= Minimal

Disclaimer: Omega Industrial Supply, Inc. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.